




Ovation™ F-165WW



About this light

The Ovation™ F-165WW is the first Fresnel-style fixture in the new Ovation™ line of theatrical lighting fixtures from CHAUVET® Professional. Its innovative LED source, produces smooth, even washes from 13° - 41°. Powered by 16 10W LEDs, Ovation™ F-165WW delivers over 1,500 lux @ 5m (13°) without a significant temperature-related drop off. The Ovation™ F-165WW delivers this class leading output with a color temperature of 3,100K and a beautiful soft field and selectable dimming curves allow this fixture to blend into existing systems. The fixture also features an easily adjustable motorized zoom and can accommodate barn doors to aid in glare reduction and beam shaping.

Features

- DMX channels: 1, 2, and 5 channels
- Operating modes
 - 1-channel: Dimmer
 - 2-channel: Dimmer, Dimmer Fine
 - 5-channel: Dimmer, Dimmer Fine, Strobe, Zoom, Zoom Reset
- Extremely quiet operation
- Smooth dimming control
- Flat field of light
- Motorized and DMX controllable zoom angle between 13° ~ 58°

At a glance

- Extremely quiet operation
- Easily adjustable motorized zoom
- Easy-access knobs for beam and output static control

Specifications

- DMX Channels: 1, 2, or 5
- DMX Connectors: 3- and 5-pin
- Light Source: 16 (Warm White) 10W (2.7A) LEDs
50,000hrs
- Efficacy: 19 LPW (13°)
34 LPW (58°)
- Strobe Rate: 0 - 20Hz
- Beam Angle: 13°/58°
- Field Angle: 24°/70.5°
- Zoom Angle: 13° - 58°
- Illuminance: 1,730 lux @ 5m
- Color Temperature: 3,100K
- Startup Temperature: -4° - 113°F (-20°C - 45°C)
- Operating Temperature: -22° - 113°F (-30°C - 45°C)
- Cable Length: 5ft (1.5m)
- Power Linking: 5 units @ 120V; 9 units @ 208V; 10 units @ 230V
- Input Voltage: Auto-ranging 100 - 240VAC 50/60Hz
- Power and Current: 170W, 1.41A @ 120V 60Hz
166W, 0.85A @ 208V 60Hz
166W, 0.78A @ 230V 50Hz
- Weight: 14.6lbs (6.6kg)
- Size: 20 x 11 x 10.5in (508 x 279 x 267mm)
- Environment: IP20, dry location
- Approvals: CE, MET